
Index

A

alarms

- red (local), 35
- timers, 36
- yellow (remote), 37
- See also* error detection; messages

automatic loop tests, 43

B

B-channels

- described, 3
- support for, 19

bit error rate error checks, 48

C

cable connection checks, 23

call tracing, 26

channels

- out-of-service conditions and restoration, 35
- status audits and changes, 19
- TN number conversion, 55
- See also* B-channels; D-channels

Clock Controller maintenance

- automatic clock recovery and switching, 81
- commands, 97
- free run (non-tracking) mode, 79
- replacing cards, 82
- tracking mode, 79

clocks

- frame slip, 51

commands

- alphabetical list for LD 96, 110
- D-channel (X11 release 17 and earlier), 15
- D-channel (X11 release 18 and later), 16
- DTI and PRI, 96
- for midnight routines, 46
- for PRI maintenance, 5
- for tracing calls, 28
- MSDL, 17, 109
- quick list, 5
- See also* LD 60; LD 96

D

DCH messages, 113

D-channel maintenance

- DCH tests 100/101, 62
- DCH tests 200/201, 64
- diagnostics from LD 96, 99
- error counts in Protocol Log, 72
- ISL recovery, 93
- MSDL local loopback tests, 66
- MSDL remote loopback tests, 69
- replacing DCHI or MSDL, 77

D-channels

- automatic loop tests, 43
- B-channel support, 19
- commands (X11 release 17 and earlier), 15
- commands (X11 release 18 and later), 16
- dedicated using DTI or PRI, 92
- described, 3, 12
- link diagnostic and remote loopback tests, 44
- local loopback test, 42
- messages, 17
- related documentation, 3
- sanity polling, 19
- self-tests, 43
- status checks, 41
- See also* channels; D-channel maintenance

DCHI cards

- DCH tests 100/101, 62
- DCH tests 200/201, 64
- described, 3, 12
- disabling/enabling, 42
- replacing, 77
- with DTI or PRI trunks, 92

DTA messages, 52, 54, 55, 121

DTC messages, 127

DTI messages, 129

E

- error counters, 57
 - in Protocol Log (PLOG), 72
- error detection
 - bit error rate thresholds, 50
 - bit error rates and bipolar violation (BPV)
 - tracking, 48
 - bit error rates and cyclic redundancy checks (CRC), 49
 - frame alignment loss, 54
 - frame slip, 51
 - yellow (remote) alarms, 47
 - See also* alarms; messages

F

fault clearing

- D-channel problems, 41
- error counters, 57
- problem solver chart, 39
- red (local) alarms, 35
- replacing PRI circuit cards, 59
- TN to channel number conversion, 55
- yellow (remote) alarms, 37
- See also* operations guides

frame alignment loss, 54

frame slip, 51

I

ISL (ISDN Signaling Link)

- maintenance, 87
- recovery, 93
- start-up, 92

J

J1/J2 ports, 12

L

LD 17

- specifying network call trace, 26

LD 20/21/22

- trunk/route/configuration information printouts, 91

LD 30

- service messages, 19

LD 32

- ISL status checks, 90

LD 36

- ISL status checks, 90

LD 60
 automatic clock recovery and switching options, 81
 Clock Controller commands, 97
 commands for midnight routines, 46
 disabling Clock Controller cards, 82
 disabling/enabling PRI loops, 42
 DTA messages, 52, 54, 55, 121
 DTI and PRI commands, 96
 ISL status checks, 90
 PRI alarm counter lists, 23, 38
 PRI card status checks, 22
 PRI card test, 24
 PRI status and alarm counter checks, 37
 remote loopback tests, 43, 44
 self-test loops, 43

LD 73
 frame alignment threshold specification, 54
 out-of-service and maintenance threshold specification, 52
 primary clock reference specification, 51

LD 96
 card and link status checks, 23
 channel status checks, 108
 DCH tests 100/101/200/201, 62, 64
 enabling/disabling message monitoring, 99
 monitor status checks, 107
 PLOG contents checks, 72
 port status checks, 22
 replacing DCHI or MSDL cards, 77
 service message initiation, 19, 20

LD 97
 disabling/enabling DCHI cards, 42

LEDs
 checking status of, 21, 22, 24
 on error counters, 58

link diagnostic and remote loopback tests, 44

local (red) alarms, 35

local loopback tests, 66

loops
 disabling/enabling, 42
 local loopback test, 66
 remote loopback tests, 44, 69
 tests, 42, 43, 44

M

maintenance service messages, 17

Meridian 1 system capacity, 4

messages
 DCH, 113
 D-channel, 17
 DTA, 52, 54, 55, 121
 DTC, 127
 DTI, 129
 MSDL, 133
 on status and error conditions, 10
 PRI, 139
 service, 17
 See also alarms; error detection

MSDL cards
 commands (X11 release 18 and later), 17
 described, 3, 13
 local loopback test, 66
 remote loopback test, 69
 replacing, 77
 with DTI or PRI trunks, 92

MSDL messages, 133

Multi-purpose Serial Data Link cards. *See* MSDL cards

N

Network Call Trace feature, 26

NT6D11AB cards, 3

NT6D80 cards, 3
 faceplate, 13
 See also MSDL cards

O

operations guide

- command quick reference list, 5
- D-channel commands quick reference lists, 15, 16
- DCHI quick reference, 12
- maintenance service messages, 17
- MSDL quick reference, 13, 17
- network call tracing, 26
- PRI status check, 21
- problem solving, 39
- start-up, 24
- system overview, 3, 4
- See also* fault clearing

out-of-service counter checks, 23

P

ports

- asynchronous, 12
- J1/J2, 12

PRI (Primary Rate Interface)

- ISL maintenance, 87
- problem solving, 39
- related documentation, 2
- replacing, 59
- start-up, 24
- status checks, 21
- See also* Clock Controller maintenance; fault clearing; operations guide

PRI cards, 4

PRI messages, 10, 139

prompts and responses. *See* LDnn

Protocol Log (PLOG), 72

Q

QPC471 Clock Controller, 82

QPC720

- checking communication path to, 42
- described, 3
- faceplate, 11

QPC757 card, 3

- faceplate, 12

See also DCHI cards

QPC775 Clock Controller, 82

R

- red (local) alarms, 35
- remote (yellow) alarms, 37
- remote loopback tests, 44, 69
- RFI filters, 93

S

- sanity polling of D-channels, 19
- self-test loops, 43
- service messages, 17
- switch settings for DCHI ports, 12

T

- TN lists, 91
- TN to channel number conversion, 55
- tracing network calls, 26

X

- X11 release 15 and later
 - D-channel interface configuration, 4
 - new maintenance message status, 20
- X11 release 16
 - message monitoring, 99
- X11 release 17
 - message monitoring, 99
- X11 release 17 and earlier
 - protocol log format and counters, 73
- X11 release 17 and later
 - enhanced D-channel reports, 113
 - Network Call Trace feature, 26
- X11 release 18 and later
 - channel status checks, 108
 - D-channels on MSDL cards, 99
 - protocol log format and counters, 74

Y

- yellow (remote) alarms, 37, 47

Meridian 1

ISDN Primary Rate Interface

Maintenance

© 1989,1997 Northern Telecom

All rights reserved

Information is subject to change without notice.

Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules, and the radio interference regulations of Industry Canada. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy, and if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at this own expense.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

Publication number: 553-2901-500

Document release: Standard 11.00

Date: October 1997

Printed in the United States of America

NORTEL
NORTHERN TELECOM